

## Survey of the S. Bdy. of fractional T. 24 N., R. 48½ E.

- Chains. From the cor. of Ts. 24 N., Rs. 48½ and 49 E., which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 49 E.,
- West, on a true line, on the S. Bdy. of sec. 36, on the S. Bdy. of the township.
- Asc. NE. slope 40 ft. over rolling land.
- 3.60 Top of spur, projects NW. Desc. SW. slope 190 ft.
- 21.30 Dry wash, drains NW. Asc. NE. slope 30 ft.
- 27.00 Top of spur, projects NW. Desc. SW. slope 100 ft.
- 38.00 Road, bears SE. to Eureka and NW. to Austin road.
- 38.60 Antelope Creek, 15 links wide, 6 ft. deep, with running water, 2 lks. wide, 2 ins. deep; course NW.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor. of sec. 36, only, with brass cap mkd:
- $\frac{1}{4}$  S36  
1926
- Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.
- Asc. E. slope 80 ft.
- 46.80 Point of spur, projects NE. Desc. W. slope 50 ft.
- 49.20 Dry wash, drains NE. Asc. E. slope 160 ft.
- 56.20 Top of spur, projects NE. Desc. W. slope 40 ft.
- 60.20 Dry wash, drains N. 10° E. Asc. E. slope 60 ft.
- 62.80 Top of spur, projects N. 10° E. Desc. W. slope 30 ft.
- 64.90 Dry wash, drains NE. Asc. E. slope 160 ft.
- 77.00 Top of spur, projects NE.
- 78.18 Intersect the W. Bdy. of the township, at a point 14 lks. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 48 E. I change the markings and accessories of this corner as follows:

T24N  
S25 | T24N  
S36 | R48½E  
R48E | S36  
1926