

Survey of the S. Bdy. of fractional T. 24 N., R. 48½ E.

Chains. Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

At the point of intersection, set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the closing cor. of Ts. 23 and 24 N., R. 48½ E., with brass cap mkd.

	T24N	
T24N	R48½E	
R48E	S36	C
S36	T23N	C
	1926	

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Land, rolling. Soil, gravelly and rocky clay of medium texture. Undergrowth, sage and scattering buck brush; fair growth of grass. No timber.

Survey of the subdivisions of fractional T. 24 N., R. 48½ E.

From the cor. of secs. 25, 30, 31 and 36, on the E. Bdy. of the township,

West, on a true line; bet. secs. 25 and 36

Desc. SW. slope 80 ft. over rolling land, through scattering juniper.

13.00 Dry wash, drains S. Asc. 70 ft. along SE. slope.

27.90 Short spur, projects S. Desc. along SW. slope 50 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor., with brass cap mkd.

	S25
¼	<u>S36</u>
	1926

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor. No bearing trees available.

Desc. broken SW. slope 120 ft.

57.30 Top of short spur, projects SW. Desc. 30 ft.

60.70 Dry wash, drains SW. Asc. 30 ft.

62.20 Top of short spur, projects SW. Desc. W. slope 100 ft. to Antelope Creek.

70.50 Road, bears SE. to Eureka and NW. to Austin road.