

Survey of the subdivisions of fractional T. 24 N., R. 48 $\frac{1}{2}$ E.

Chains.

73.00

Antelope Creek, running water, 3 lks. wide, 2 ins. deep, course NW. Asc. 40 ft.

78.36

Intersect the W. Bdy. of the township, at a point 18 lks. south of the cor. of secs. 19, 24, 25 and 30, which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 48 E. I change the markings of this corner to refer to secs. 24 and 25, only, and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

At the point of intersection, set and iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 25 and 36, with brass cap mkd.

| | |
|------|---------------------|
| T24N | T24N |
| S25 | S25 C |
| R48E | S36 C |
| S25 | R48 $\frac{1}{2}$ E |
| | 1926 |

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of the cor. No bearing trees available.

Land, rolling. Soil, gravelly and rocky clay of medium texture. Undergrowth, sage; fair growth of grass.

Timber, scattering juniper.

I destroy all markings pertaining to sec. 30 on the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the W. Bdy. of the township, from which corner I run South 16 lks. distant. Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 36, only, with brass cap mkd.

| | |
|---------------|------|
| $\frac{1}{4}$ | |
| S36 | |
| | 1926 |

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of the cor. No bearing trees available.

From the cor. of secs. 19, 24, 25 and 30, on the E. Bdy. of the township, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 49 E.,