

Survey of the subdivisions of fractional T. 24 N., R. 49<sup>8/2</sup> E.

Chains. A pinon pine 14 ins. in diam., bears S.  $89\frac{1}{4}^{\circ}$  E., 66 lks. distant, marked CC T24N R48 $\frac{1}{2}$ E S25 BT  
Land, mountainous. Soil, gravelly and rocky clay of medium texture. Undergrowth, sage; fair growth of grass. Timber, juniper and pinon pine.

I destroy all markings on the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, on the W. Bdy. of the township, on the E. side of the line, from which corner I run South 23 lks., set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 25, only, with brass cap mkd.

$\frac{1}{4}$   
S25  
1926

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of the cor. No bearing trees available.

From the corner of sec. 13, 18, 19 and 24, on the E. Bdy. of the township, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 49 E., West, on a true line, bet. secs. 13 and 24.  
Asc. E. slope over rolling land.

- 5.10 Top of ridge, bears NW. and SE. Desc. W. slope 260 ft. to dry wash.
- 5.50 Spring designated as C, bears N.  $25^{\circ} 45'$  E. See field notes of T. 24 N., R. 49 E.
- 20.40 Dry wash, drains SW. Asc. SE. slope 50 ft.
- 27.80 Top of spur, projects S. Desc. W. slope 80 ft.
- 32.70 Dry wash, drains S. Asc. E. slope 20 ft.
- 36.10 Top of spur, projects S. Desc. W. slope 40 ft.
- 38.40 Dry wash, drains S. Asc. E. slope 20 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground, to solid rock, in a mound of stone 16 ins. high, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S13  
S24  
1926