

Survey of the subdivisions of fractional T.24 N., R. 48 $\frac{1}{2}$ E.

- Chains. From the cor. of secs. 7, 12, 13 and 18, on the E. Bdy. of the township, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 49 E., West, on a true line, bet. secs. 12 and 13. Desc. 90 ft. over rolling land, through scattering juniper and pinon pine.
- 14.40 Top of low spur, projects S. Desc. 20 ft.
- 16.00 Dry wash, drains S. 30° W. Asc. gradually 20 ft. over SE. slope.
- 21.90 Top of spur, projects S. 30° W. Desc. SW. slope 80 ft.
- 36.90 Slope changes to SE. Asc. 20 ft.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
- $$\frac{1}{4} \frac{S12}{S13}$$
 1926
- from which
- A juniper 6 ins. in diam., bears N. 6° E., 32 lks. distant, marked $\frac{1}{4}$ S12 BT
- A juniper 6 ins. in diam., bears S. 70° E., 129 lks. distant, marked $\frac{1}{4}$ S13 BT
- Desc. W. slope 40 ft.
- 43.00 Dry wash, drains SW. Asc. SE. slope 70 ft.
- 57.10 Top of spur, projects SW. Desc. W. slope 120 ft.
- 66.70 Dry wash, drains SW. Asc. E. slope 100 ft.
- 78.00 Top of spur, projects SW. Desc. NW. slope 30 ft.
- 78.32 Intersect the W. Bdy. of the township, at a point 23 lks. South of the cor. of secs. 1, 6, 7 and 12, which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 24 N., R. 48 E. I destroy all markings on this corner pertaining to the east side of the line and mark T24N R48 $\frac{1}{2}$ E S12 thereon.
- At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 15 ins. in the ground, to solid rock, in a mound of stone, for the closing cor. of secs.