

## Retracement of Subdivisions, T. 23 N., R. 49 E.

## Chains

80.37 Fall 20 lks. N. of the original cor. of secs. 7, 8, 17 and 18, hereinafter described.

The bearing and distance of W.  $\frac{1}{2}$  mile is therefore  
S.  $89^{\circ}51'$  W., 40.19 chs.

From the cor. of secs. 7, 8, 17 and 18.

West, on retracement line bet. secs. 7 and 18.

40.09 S. of line 8 lks. dist. is the original  $\frac{1}{4}$  sec. cor., hereinafter described.

The bearing and distance of this half mile is therefore  
S.  $89^{\circ}53'$  W., 40.09 chs.

Continue same line with continuous measurement.

79.53 Fall 11 lks. N. of the original cor. of secs. 7 and 18 on the W. bdy. of tp., hereinafter described.

The bearing and distance of W.  $\frac{1}{2}$  mile is therefore  
S.  $89^{\circ}57'$  W., 39.44 chs.

## RESURVEY OF SUBDIVISIONS, T. 23 N., R. 49 E.

Return to the original cor. of secs. 3, 4, 33 and 34

on S. bdy. of tp., which is a quartzite stone, showing  
12x12x6 ins. above ground, firmly set, plainly marked  
with 3 notches on E. and W. edges; no accessories.

Alongside of stone, set an iron post, 3 ft. long, 2 ins.  
dia., 26 ins. in the ground, for cor. of secs. 3, 4,  
33 and 34, with brass cap marked

T23N	R49E
S33	S34
S4	S3
T22N	
1927	

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  
Corner situated on a slight S. exposure on rolling bench.  
Thence,

N.  $0^{\circ}12'$  E., on resurvey line bet. secs. 33 and 34.

Over rolling and broken bench land facing W., through