

Resurvey of Subdivisions, T. 23 N., R. 49 E.

Chains

post, 3 ft. long, 1 in. dia., 26 ins. in the ground,
for $\frac{1}{4}$ sec. cor., marked on brass cap

$\frac{1}{4}$ S7
S18
1927

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of
cor.

Thence, S. $89^{\circ}57'$ W.

64.00 Top of low spur from mountain, slopes S. 85° E.; continue
gentle ascent over S. exposure, near top of spur.

79.53 On S. slope, 140 ft. above $\frac{1}{4}$ sec. cor.,
The original cor. of secs. 7 and 18 on W. bdy. of tp.,
which is a gray granite stone, showing 18x16x12 ins.,
above ground, firmly set, plainly marked with 4
grooves on S. and 2 grooves on N. face; witnessed by
a mound of stone, E. of cor.

Note: This cor. stands North, 153 chs. dist. from the
cor. of secs. 12 and 13, T.23 N., R.48 E.

Land, rolling with general E. exposure and drainage.

Soil, gravelly, clay and stony; 3rd rate.

Undergrowth, short sagebrush and grass.

No timber.

SURVEY OF PORTION OF SOUTH BOUNDARY, T.23 N., R.49 E.

From the cor. of secs. 3, 4, 33 and 34 on S. bdy. of tp.,
heretofore described.

East, on true line along S. bdy. of tp., on S. bdy. sec.
34.

Over rolling bench land, through dense sagebrush;
gradually desc. SE. slope, 15 ft. to

10.60 Draw, near head, drains S. 60° W.; ascend 40 ft. over
gradual W. slope.

30.00 Top of gentle rise on bench, bears NE. and SW.; descend
25 ft. over E. slope.

35.90 Bottom of shallow draw, near head, drains SW.; gentle