

Survey of North Boundary, T. 23 N., R. 49 E.

Chains

of stone, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S5 \\ \frac{1}{4} \text{ ---} \\ S5 \\ 1927 \end{array}$$

At base of monument, deposit a granite stone, 8x6x3 ins., marked with a cross (X).

Continue over general S. and SE. slopes.

46.40 Shallow swale, drains S.80°E.

63.00 Low spur, slopes S. 5 chs. to end.

79.00 Top of high, divide ridge, 80 ft. above $\frac{1}{4}$ sec. cor., bears N.30°E. and S.10°W.

80.00 On gentle W. slope on ridge,
Set an iron post, 3 ft. long, 2 ins. dia., 18 ins. in the ground to bedrock, and supported by a large mound of stone, 5 ft. base, for cor. of secs. 5, 6, 5 and 6, with brass cap marked

$$\begin{array}{c|c} T23\frac{1}{2}N & R49E \\ \hline S6 & S5 \\ \hline S6 & S5 \\ \hline T23N \\ 1927 \end{array}$$

at base of monument, deposit a granite stone, 8x8x6 ins., marked with a cross (X).

Land, rolling mountainous with general S. to SE. exposure and drainage.

Soil, gravelly clay, and rocky, lying on hard-pan of cemented gravel, and rock subsoil; 3rd rate.

Undergrowth, dense sagebrush. No timber.

West, on true line bet. secs. 6 and 6.

Over rolling mountainous land, through dense sagebrush; descend from divide ridge over W. and NW. slopes.

17.80 Small draw, near head, 240 ft. below cor., drains N.70°W.; asc. 90 ft. to

21.15 Low spur, slopes N.70°W. 10 chs. to end; desc. gradual W. slope.

31.95 Road, bears N. to Cortez, and S. to Eureka, Nev.