Subdivision of T. 23 N., R. 49 E.

	Subdivision of 1. 25 N., A. 49 E.
Chains	
	At base of monument, deposit a granite stone, 7x6x6 ins.,
	marked with a cross (X).
	Corner situated on gentle SE. slope, 1 ch. S. of low
	rise, bears NE. and SW.
	Land, rolling mountainous with general NW. and N.
5	exposure and drainage into Antelope Creek.
	Soil, gravelly clay, mixed with some scattered rock,
	lying on cemented gravel and clay subsoil; 3rd rate.
	Undergrowth, dense sagebrush, scattered service brush.
-	No timber.
to .	
	SUBDIVISION OF T. 23 N., R. 49 E.
	SUBDIVISION OF I. 20 N., N. 45 E.
•	From the cor. of secs. 35 and 36 on S. bdy. of tp.,
	hereinbefore described.
	N. 0°01' W., bet. secs. 35 and 36.
	Over rolling mountainous land, through scattered timber
	and dense undergrowth; asc. steep S. slope, 70 ft.
5.10	Ridge, bears N.60°E., and W.; a saddle bears N.60°E.
74.54	about 5 chs. dist.; desc. NE. slope, 125 ft.
16.00	Small draw, drains N.20°W.; thence along a gradual W.
	slopes, descending.
25.80	Begin descent over N. slope into draw.
30.50	Draw, 255 ft. below ridge, drains W. for 8 chs., thence
	N.30°W.; ascend S. slope, entering dense timber, bears
	E. and W.
36.00	Top of steep ascent from draw, slope changes to gradual
	SW. and W.
40.00	On a gradual W. slope, 125 ft. above draw,
	Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in
	the ground to rock, and supported by a mound of stone,
	for \frac{1}{4} sec. cor., with brass cap marked
	4 075
	S35 S36
	1927

from which