

Subdivision of T. 23 N., R. 49 E.

Chains	
	At base of monument, deposit a granite 8x6x6 ins., marked with a cross (X). Other accessories impracticable.
53.00	Top of rise, 25 ft. above cor., bears NW. and SE.
53.85	Road, bears NW. to Cortez, and SE. to Eureka.
54.50	Begin descent W. slope of 50 ft. into draw, bears NW. and SE.
60.25	Dry wash, 20 lks. wide, 1 ft. deep, in bottom of draw, drains SE.; asc. gentle E. slope, 65 ft. to
80.38	The cor. of secs. 5, 6, 7 and 8. Land, rolling with general SE. and S. exposure; drainage SE. Soil, gravelly and gravelly clay, mixed with scattered rock; 3rd rate. Undergrowth, dense sagebrush. No timber.
	<hr/>
	S. 89°55' W., on true line bet. secs. 6 and 7. Over rolling land with general easterly slope, through dense sagebrush; gently ascending.
16.80	Swale, 15 ft. deep, drains SE.
40.00	On a gentle S. slope, 85 ft. above sec. cor., Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked <div>$\begin{array}{r} S6 \\ \frac{1}{4} \overline{) S7} \\ 1927 \end{array}$</div>
	At base of monument, deposit a granite rock, 10x8x8 ins., marked with a cross (X). And place a small mound of stone around post. Other accessories impracticable.
42.00	Begin descent over SW. slope of 35 ft. into swale.
52.50	Swale, drains S.80°E.; asc. rolling E. slope 175 ft. to cor.
78.25	Top of spur, projects S.70°E.; thence along top of same, slight S. slope.
79.36	Intersect W. bdy. of tp., North, 1.53 chs. dist. from the original cor. of secs. 1 and 12, T.23 N., R. 48 E.,