

Establishment of $\frac{1}{4}$ sec. cors. on portion of
West Boundary, T. 23 N., R. 48 E.

Chains

ESTABLISHMENT OF $\frac{1}{4}$ SEC. CORS. ON PORTION OF
WEST BOUNDARY, T. 23 N., R. 49 E.

From the original cor. of secs. 7 and 18, on W. bdy. of
tp., heretofore described on page 20 of these notes.
North, on W. bdy. of sec. 7, T. 23 N., R. 49 E.

38.47 The original $\frac{1}{4}$ sec. cor. of sec. 12, which is an iron
post, 1 in. dia., extending 12 ins. above ground,
firmly set, properly marked and witnessed as described
in official notes of T. 23 N., R. 48 E. (this cor. is
N. 40.00 chs. from the cor. of secs. 12 and 13)

40.00 Point midway bet. the cor. of secs. 7 and 18, and the
closing cor. of secs. 6 and 7,

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in
the ground for $\frac{1}{4}$ sec. cor. of sec. 7, T. 23 N., R.
49 E., with brass cap marked

$\frac{1}{4}$
S7

1927

At base of post, deposit a granite rock, 6x4x4 ins.,
marked with a cross (X). And place a small mound of
stone around post. No other accessories available.

78.47 The original cor. of secs. 1 and 12, T. 23 N., R. 48 E.,
which is an iron post, 2 ins. dia., extending 16 ins.
above ground, firmly set, properly marked and witnessed
as described in official records of T. 23 N., R. 48 E.

80.00 The closing cor. of secs. 6 and 7, T. 23 N., R. 49 E.,
as established by me, and described on page 83, these
notes.

North, on W. bdy. sec. 6.

38.47 The original $\frac{1}{4}$ sec. cor., sec. 1, T. 23 N., R. 48 E.,
which is an iron post, 1 in. dia., extending 12 ins.
above ground, firmly set, properly marked and witnessed
as described in official records of T. 23 N., R. 48 E.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in