

Establishment of Quarter-Section Corners on
North Boundary, T. 23 $\frac{1}{2}$ N., R. 49 E.

Chains

from which

A pinon, 7 ins. diam., bears S. 53 $\frac{3}{4}$ ° E., 103 lks.
dist., marked $\frac{1}{4}$ S 3 BT

A pinon, 14 ins. diam., bears S. 81 $\frac{1}{2}$ ° W., 64 lks.
dist., marked $\frac{1}{4}$ S 3 BT

42.83 The $\frac{1}{4}$ sec. cor. of secs. 33, T. 24 N., R. 49 E., an iron
post, 1 in. dia., extending 12 ins. above ground,
firmly set, marked and witnessed as described in
official records of T. 24 N., R. 49 E.

79.89 The closing cor. of secs. 3 and 4, T. 23 $\frac{1}{2}$ N., R. 49 E.,
hereinafter described.

West, on N. bdy. sec. 4.

2.94 The cor. of secs. 32 and 33, T. 24 N., R. 49 E., an iron
post, 2 ins. dia., extending 10 ins. above ground,
firmly set, marked and witnessed as described in
official records of T. 24 N., R. 49 E. I change the
markings on S. half of post from T23N to read T23 $\frac{1}{2}$ N.

39.98 Midpoint bet. the closing cors. of secs. 3 and 4, and
4 and 5; set an iron post, 3 ft. long, 1 in. dia.,
26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 4,
T. 23 $\frac{1}{2}$ N., R. 49 E., with brass cap marked

$\frac{1}{4}$ S 4
1927

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
S. of cor.

42.94 The $\frac{1}{4}$ sec. cor. of sec. 32, T. 24 N., R. 49 E., an iron
post, 1 in. dia., extending 12 ins. above ground,
firmly set, properly marked and witnessed as described
in official records of T. 24 N., R. 49 E.

79.96 The closing cor. of secs. 4 and 5, T. 23 $\frac{1}{2}$ N., R. 49 E.,
hereinafter described.

West, on N. bdy. sec. 5.

2.98 The cor. of secs. 31 and 32, T. 24 N., R. 49 E., an iron