

Establishment of Quarter-Section Corners on
North Boundary, T. 23½ N., R. 49 E.

Chains

post, 2 ins. diam., firmly set in ground and in a mound of stone, properly marked and witnessed as described in official records of T.24 N., R. 49 E.

40.00 Midpoint bet. the closing cors. of secs. 4 and 5, and 5 and 6; set an iron post, 3 ft. long, 1 in. dia., 10 ins. in ground to rock, and supported by a large mound of stone, for ¼ sec. cor. sec. 5, T.23½ N., R.49 E., with brass cap marked

¼ S5

1927

At base of post, deposit a granite stone, 11x10x8 ins., marked with a cross (X) No other accessories available.

Corner situated on gradual NW. slope near top of ridge.

42.98 The ¼ sec. cor. of sec. 31, T. 24 N., R. 49 E., an iron post, 1 in. dia., extending 12 ins. above ground, firmly set, marked and witnessed as described in official records of T. 24 N., R. 49 E.

80.00 The closing cor. of secs. 5 and 6, T 23½ N., R. 49 E., hereinafter described.

West, on N. bdy. sec. 6.

1.17 The cor. of Ts. 24 N., Rs. 48½ and 49 E., an iron post, 3 ins. dia., extending 12 ins. above ground, firmly set, marked and witnessed as described in official records of T. 24 N., R. 49 E. I change the markings on S. half of post from T23N to read T23½N.

40.00 True point for ¼ sec. cor. of sec. 6 falls in W. edge of Antelope Creek with 6 ft. vertical bank where cor. cannot be perpetuated. No cor set here.

40.20 Or point 20 lks. W. of true cor point,
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for witness cor. to the ¼ sec. cor. of sec. 6; T. 23½ N., R. 49 E., with brass cap marked

¼ S6 WC

1927