

ESTABLISHMENT OF QUARTER-SECTION CORNER ON  
WEST BOUNDARY OF T. 23 $\frac{1}{2}$  N., R. 49 E.

Chains

with brass cap marked.

|  $\frac{1}{4}$   
| S6  
1927

At base of post, deposit a granite stone, 8x6x3 ins.,  
marked with a cross (X). No other accessories available.  
Corner situated on a gradual N. slope, about 50 lks. N.  
of top of spur, projecting NE.

- 41.75 The original  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, an iron  
post, 1 in. dia., extending 12 ins. above ground,  
firmly set, marked and witnessed as described in  
records of T. 24 N., R. 48 E. This cor. now refers to  
sec. 36, T. 24 N., R. 48 E. only, I efface the marks  
on E. half of post, leaving same marked

|  $\frac{1}{4}$   
S36  
1915

- 81.61 The closing cor. of T. 23 $\frac{1}{2}$  N., R. 49 E. and T. 24 N.,  
R. 48 $\frac{1}{2}$  E., heretofore described.

SURVEY OF EAST BOUNDARY OF FRACTIONAL T. 23 $\frac{1}{2}$  N., R. 49 E.

From the cor. of Ts. 23 and 23 $\frac{1}{2}$  N., Rs. 49 and 50 E.,  
a 3 in. iron post, recently established by me under  
this group and described in survey of T. 23 N., R. 49 E.

Thence

North, on E. bdy. of T. 23 $\frac{1}{2}$  N., R. 49 E., bet. secs.  
1 and 6.

Over rolling bench land facing W., through scattered  
timber and dense sagebrush.

- 2.25 Old road at bend, bears N.20°E. and S.20°E.  
6.70 Small ravine, 10 ft. deep, drains W.  
38.30 Shallow swale, drains N.80°W.  
40.00 On a slight SW. exposure on bench,  
Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in