

Subdivision of T. 23 $\frac{1}{2}$ N., R. 49 E.SUBDIVISION OF T. 23 $\frac{1}{2}$ N., R. 49 E.

From the cor. of secs. 1, 2, 1 and 2, on S. bdy. of tp.,
recently established under this group and described
in survey of T. 23 N., R. 49 E.

Thence

N. 0°01' W., on true line bet. secs. 1 and 2.

Over rolling land with a general easterly exposure,
through dense timber and undergrowth; slight ascent
along S. slope.

5.30 Top of rise, 5 ft. above cor., bears NE. and SW.; desc.
N. slope, 40 ft. to wash; and enter scattered timber
bears E. and SW.


12.70 Main road bet. Tonkin and 3 Bar ranches, bears NE. and
SW.

14.70 Wash, 20 lks. wide, 2 ft. deep, in bottom of wide swale,
drains NE.; gently asc. along rolling E. slope.

24.70 Swale, drains E.

30.80 Low, rolling spur, 35 ft. above wash, slopes off NE.;
desc. N. slope 45 ft. to $\frac{1}{4}$ sec. cor.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked



from which

A pinon, 9 ins. diam., bears N. 10 $\frac{1}{2}$ ° E., 285 lks.
dist., marked $\frac{1}{4}$ S1 BT
A pinon, 10 ins. diam., bears N. 2° W., 245 lks.
dist., marked $\frac{1}{4}$ S2 BT

Corner stands in bottom of wide, shallow swale, drains
nearly E.

44.00 Top of low spur, 15 ft. above cor., projects N. 70° E.;
desc. rolling N. slope.

57.68 Wire fence, bears N. 71° W. and S. 71° E.

59.20 Bottom of draw, 40 ft. below spur, drains S. 70° E., from
SW.; thence across bottom.