

Survey of a portion of the subdivisions of T.24 N., R.49 E.

Chains.

- 43.00 Dry wash, drains SE. Asc. S. slope 40 ft.
- 49.50 Top of low spur, projects SE. from SW. Desc. N. slope 20 ft.
- 53.90 Dry wash, drains E. Asc. SW. slope 150 ft.
- 75.84 Intersect the N. Bdy. of the township, at a point, East, 1.90 chs. distant, from the cor. of secs. 3, 4, 33 and 34, which is an iron post, 2 ins. in diam., firmly set, properly marked and witnessed, as described in the field notes of T. 25 N., R. 49 E. I destroy all markings and accessories pertaining to the south sections and mark the cor. T24N R49E S4 on the S. side of post.
- At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 3 and 4, with brass cap mkd.

T25N R49E
S34
S4 S3
T24N R49E
C C
1926

from which

A juniper, 10 ins. in diam., bears S. $44\frac{1}{2}^{\circ}$ E., 55 lks. distant, marked CC T24N R49E S3 BT

A juniper, 6 ins. in diam., bears S. $64\frac{1}{2}^{\circ}$ W., 44 lks. distant, marked CC T24N R49E S4 BT

Land, rolling. Soil, gravelly clay of medium texture.

Undergrowth, sage; fair growth of grass. Timber, juniper and pinon pine.

I destroy all markings pertaining to the south section on the $\frac{1}{4}$ sec. cor. bet. secs. 3 and 34, on the N. Bdy. of the township, which is an iron post, 1 in. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 25 N., R. 49 E., from which corner, I run East

- 1.85 Set an iron post, 3 ft. long, 1 in. in diam., 20 ins. in the ground, to solid rock, and 16 ins. in a mound of stone, for the $\frac{1}{4}$ sec. cor. of secs. 3, only, with brass cap mkd.