

Survey of a portion of the subdivisions of T. 24 N., R. 49 E.

Chains. N. $0^{\circ} 01'$ W., bet. secs. 5 and 6.

Desc. NW. slope 140 ft. over mountainous land, through scattering to medium growth of juniper and pinon pine.

4.60 Dry wash, drains NE. Asc. SE. slope 60 ft.

6.50 Top of spur, projects E. Desc. NE. slope 30 ft.

11.50 Dry wash, drains SE. Asc. S. slope 200 ft.

21.90 Top of spur, projects E. Desc. N. slope 220 ft.

31.20 Dry wash, drains E. Asc. S. slope 200 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 15 ins. in the ground, to solid rock, in a mound of stone 20 ins. high, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S6 | S5
1926

from which

A pinon pine, 12 ins. in diam., bears N. $76-3/4^{\circ}$ E., 234 lks. distant, marked $\frac{1}{4}$ S5 BT

A pinon pine, 16 ins. in diam., bears S. 87° W., 64 lks. distant, marked $\frac{1}{4}$ S6 BT

Asc. S. slope 10 ft.

41.90 Top of spur, projects E. Desc. N. slope 390 ft.

52.00 Dry wash, drains N. 70° E. Asc. S. slope 250 ft.

63.60 Top of spur, projects N. 60° E. Desc. N. slope 230 ft.

72.50 Dry wash, drains E. Asc. S. slope 110 ft.

75.83 Intersect the N. Bdy. of the township, E., 1.00 chs.

distant from the cor. of secs. 5, 6, 31 and 32, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 25 N., R. 49 E. I destroy all markings on this cor. south of the line and mark S6 T24N R49E thereon and destroy accessories pertaining to the south township.

At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 5 and 6, with brass cap mkd.