

DEPENDENT RESURVEY OF PORTION OF SUBDIVISIONS  
T. 19 N., R. 39 E.

Chains	
40.22	Proportionate point for $\frac{1}{4}$ sec. cor. Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 13 only, with brass cap mkd $\frac{1}{4} S13$ $1929$
40.43	Raisé a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. Westing of 40.00 chs. from the cor. of secs. 7, 12, 13, and 18 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd $\frac{1}{4} S12$ $1929$
57.40	At base of post deposit a mkd(X) granite stone, 4x4x4 ins. Wash, 10 lks. wide, 2 ft. deep, drains S. $30^{\circ}$ E.
73.10	Wash in draw, 10 lks. wide, 1 ft. deep, drains S. $50^{\circ}$ E.
80.44	The cor. of secs. 7, 12, 13, and 18 Land, W. 10 chs. rough mountainous, E. 70 chs. rolling mountainous. Soil, rocky and gravelly, 3rd and 4th rate. Timber, scattering pinon, juniper. Undergrowth, scattering sage and shadscale. General drainage, SE. Grazing, poor.
Chains	SURVEY OF PORTION OF SUBDIVISIONS T. 19 N., R. 39 E.
	From the cor. of secs. 11 and 12 N. $0^{\circ} 01'$ W., between secs. 11 and 12 Over rough mountainous land through scattering timber Desc. along general NE. slope 65 ft. to
4.05	Head of ravine, drains SE. Asc. SE. slope 125 ft. to
17.80	Rocky spur, projects E. Desc. along broken NE. slope 260 ft. to 44.90
38.29	Northing of 40.00 chs. from the cor. of secs. 11 and 14 Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in the