

DEPENDENT RESURVEY OF PORTION OF
SEVENTH STANDARD PARALLEL NORTH THROUGH R. 48 E.

Chains structured by placing the regulation iron posts along-
side the original monuments. All missing section cor-
ners were restored by double proportionate measurement
and the missing quarter section corners were restored
by single proportionate measurement on line between
the section corners.

DEPENDENT RESURVEY OF PORTION OF
SEVENTH STANDARD PARALLEL NORTH THROUGH R. 48 E.

Reestablishment of surveys executed by
Hatch, Eaton and Smyles, U.S. Deputy Surveyors in 1872
Random lines.

- From the standard $\frac{1}{4}$ sec. cor. on S. bdy. of sec. 32.
S. $89^{\circ} 55'$ W., along S. bdy. of sec. 32.
- 0.70 Intersect the closing corner of Secs. 4 and 5, T. 35 N.,
R. 48 E., M.D.M., an iron post 2 ins. in diam., marked as
described in the Field Notes of said Township.
- 40.61 No evidence of the standard cor. of secs. 31 and 32, could
be found.
I continue on same line with continuous measurement.
- 80.89 Intersect the closing corner of Secs. 5 and 6, T. 35 N., R. 48 E.,
M.D.M., an iron post 2 ins. in diam. marked as described
in the Field Notes of said Township.
- 81.44 Intersect the standard $\frac{1}{4}$ sec. cor. on S. Bdy. of Sec. 31.
The course of the line between the standard $\frac{1}{4}$ sec. cor.
on S. Bdy. of Sec. 32 and the standard $\frac{1}{4}$ sec. cor. on S.
Bdy. of Sec. 31, therefore is S. $89^{\circ} 55'$ W. and the propor-
tionate distance of each half mile is 40.72 chs.

True Lines.

From the standard $\frac{1}{4}$ sec. cor. on S. bdy. of sec. 31, which is
an iron post, 1 in. diam., extending 12 ins. above the
ground, with brass cap marked

$\frac{1}{4}$ S 31

1914

Cor. is witnessed by pits, 18 x 18 x 12 ins., E. and W.

100 ft. post, 3 ft. distant.

Thence

N. $89^{\circ} 55'$ E., along S. bdy. of sec. 31.

Descend gentle E. slope over rolling land, through medium
dense undergrowth.