

DEPENDENT RESURVEY OF SUBDIVISION OF T. 36 N., R. 48 E.

Chains

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground with brass cap marked

18 has 28  $\frac{1}{4}$  sec. 1 | S 6  
1930

Set the old willow stake alongside of post, and raise a mound of stone, 2 ft. base, 1  $\frac{1}{2}$  ft. high W. of cor.

Thence North, with continuous measurement.

45.30 Wash, 10 lks. wide, 3 ft. deep, in draw, 10 ft. below top of ascent, drains SE. about 3 chs., thence S.; ascend S. slope.

49.00 Edge of bench, 60 ft. above wash, brs. NW. and SE.; thence over rolling bench land sloping gently to SE.

75.10 Wash, 10 lks. wide, 2 ft. deep, in swale, drains SE.

80.93 The reconstructed cor. of Ts. 36 and 37 N., Rs. 47 and 48 E., for description of which see the field notes of dependent resurvey of T. 37 N., R. 48 E.

Land, rolling.

Soil, sandy and gravelly loam; 1st to 3rd rate.

No timber.

Undergrowth, dense and medium dense sagebrush from 2 to 4 ft. high; medium growth of grass and weeds.

Good grazing land.

DEPENDENT RESURVEY OF SUBDIVISIONS OF T. 36 N., R. 48 E.

Reestablishment of surveys executed by Hatch, Eaton and Smyles, U.S. Deputy Surveyors in 1872, and by McClellan and Bridges, U. S. Deputy Surveyors in 1884.

From the standard cor. of secs. 35 and 36, on S. bdy. of Tp., which is an iron post, 3 ins. diam., extending 12 ins. above the ground, with brass cap marked

T36N | R48E  
S 35 | S 36  
SC