

## DEPENDENT RESURVEY OF SUBDIVISION OF T. 36 N., R. 48 E.

Chains

$$\begin{array}{c} \frac{1}{2} \\ | \\ S 2 | S 1 \\ | \\ 1930 \end{array}$$

- Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high W. of cor.
- 79.56 The reconstructed cor. of secs. 1, 2, 35 and 36, on N. bdy. of Tp., for description of which see the field notes of dependent resurvey of T. 37 N., R. 48 E. Land, rolling hills with a NW. exposure and drainage. Soil, sandy and gravelly loam from 8 to 12 ins. deep, on a hard, rocky clay subsoil; 2nd to 3rd rate. No timber. Undergrowth, medium dense sagebrush from 1 to 3 ft. high; medium growth of grass and weeds. Good grazing land.
- 
- From the standard cor. of secs. 34 and 35, on S. bdy. of Tp., which is an iron post, 3 ins. diam., extending 12 ins. above the ground, with brass cap marked
- |      |      |
|------|------|
| T36N | R48E |
| S 34 | S 35 |
| SC   |      |
- 1914
- Cor. is witnessed by pits and a mound of earth.
- Thence
- N.  $0^{\circ} 02' E.$ , bet. secs. 34 and 35.
- Ascend gentle E. slope over rolling land, through medium dense undergrowth.
- 19.50 Spur, 45 ft. above sec. cor., projects NE.; thence descend along gentle E. slope.
- 39.91 $\frac{1}{2}$  Proportionate point, on gentle E. slope, 70 ft. below spur.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap marked