

DEPENDENT RESURVEY OF SUBDIVISION OF T. 36 N., R. 48 E.

Chains

From the standard cor. of secs. 32 and 33, on S. bdy. of Tp., which is an iron post, 3 ins. diam., extending 12 ins. above the ground, with brass cap marked

T36N	R48E
S 32	S 33
SC	

1914

Cor. is witnessed by pits and a mound of earth.

Thence

N. 0° 36' W., bet. secs. 32 and 33.

Descend gentle N. slope over rolling hills, through medium dense undergrowth.

20.40 Draw, 120 ft. below sec. cor., drains NW. about 5 chs., thence W.; ascend gentle S. slope.

33.00 Spur, 90 ft. above draw, projects W.; descend.

39.92½ Proportionate point, in head of draw, 10 ft. below spur, drains W.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for ¼ sec. cor., with brass cap marked

¼	
S 32	S 33

1930

Raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor.

Ascend gentle SW. slope.

43.00 Spur, 10 ft. above ¼ sec. cor., projects NW.; descend gentle E. slope.

79.85 Proportionate point, on gentle E. slope 220 ft. below spur.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 28, 29, 32 and 33, with brass cap marked

T36N	R48E
S 29	S 28
S 32	S 33

1930