

DEPENDENT RESURVEY SOUTH BOUNDARY OF T. 38 N., R. 48 E.

Chains

... 5; 17 and 20; 7 and 8; and 17 and 18 were the only original corners found. These corners were reconstructed by placing the regulation iron posts monument alongside the original monument. All missing section corners were restored by double proportionate measurement and the quarter section corners restored by single proportionate measurement on line between the section corners.

DEPENDENT RESURVEY SOUTH BOUNDARY OF T. 38 N., R. 48 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY HATCH, EATON, AND SMYLES, U.S. DEPUTY SURVEYORS IN 1872, AND T. K. STEWART, U.S. DEPUTY SURVEYOR IN 1884.

Random Lines.

From the cor. of Ts. 37 and 38 N., Rs. 47 and 48 E., hereinafter described.

East, bet. secs. 6 and 31.

39.13 Fall 9 lks. S. of the original $\frac{1}{4}$ sec. cor.
The bearing of this half mile therefore is N. 89° 52'E., and the distance is 39.13 chs.

From the $\frac{1}{4}$ sec. cor., continue East, bet. secs. 6 and 31, with continuous measurement.

78.55 Fall 8 lks. N. of the original cor. of secs. 5, 6, 31 and 32.
The bearing of this half mile therefore is S. 89° 53'E., and the distance is 39.42 chs.

From the cor. of secs. 5, 6, 31 and 32. S. 88° 14'E., along S. bdy. of T. 38 N., R. 48 E., making careful search at intervals of 39.96 and 79.92 chs. for $\frac{1}{4}$ sec. and sec. corners, and at

394.15 Set temp. cor. for Ts. 37 and 38 N., Rs. 48 and 49 E., From temp. cor. of Ts. 37 and 38 N., Rs. 48 and 49 E. S. 88° 31'E., along S. bdy. of T. 38 N., R. 49 E.,