


DEPENDENT RESURVEY EAST BOUNDARY OF T.39 N., R.48 E.

Chains

Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground on solid rock and in a mound of stone for cor. of secs. 1, 6, 7, and 12, with brass cap marked



Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.; also, deposit a basalt stone, 5x4x3 ins., marked with a cross (+) on one face at base of monument.

Land, rolling and broken; general SW. exposure and drainage.

Soil, gravelly and sandy clay loam with loose rock on surface; 2nd. and 3rd. rates.

No timber.

Undergrowth, sagebrush and native grasses.

N.0°47'W., bet. secs. 1 and 6.

Gradually descend NW. slope over rolling land through short undergrowth.


23.70 Draw, 90 ft. below sec. cor., drains S.60°W.; ascend.

32.15 Low ridge, divide between Willow and Rock Creeks, bears E. and W.; gradually descend.

37.30 Road, (old) bears NW. and E., in draw draining NW.

40.12 Proportionate point.

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ¼ sec. cor., with brass cap marked



Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

40.80 Small draw, drains S.70°W. about 5 chs. to junction with main draw, thence NW.; gradually ascend.

59.75 Spur, 25 ft. above ¼ sec. cor., projects N.60°W.; descend 70 ft. over rocky and broken N. slope to