

DEPENDENT RESURVEY SOUTH BOUNDARY OF T.39 N., R.48 E.

Chains

80.24 The original cor. of Tps. 39 and 40 N., Rs. 48 and 49 E., which is a trap stone, 12x4x4 ins., marked with 6 grooves on E. and W. faces and N on N. face; cor. firmly set in an old deeply embedded mound of stone. Alongside cor., set an iron post, 3 ft. long, 3 ins. in dia., 28 ins. in the ground, with brass cap marked

T40N	
R48E	R49E
S36	S31
S1	S6

T39N
1929

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor. Land, rolling and broken; general drainage N. and S. from divide bet. Willow and Rock Creeks. Soil, gravelly, sandy clay loam and rock; 2nd. to 4th. rates. No timber. Undergrowth, sagebrush and native grasses.

DEPENDENT RESURVEY SOUTH BOUNDARY OF T.39 N., R.48 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY HATCH, EATON, AND SMYLES, U. S. DEPUTY SURVEYORS IN 1872.

Random Lines.

From the cor. of Tps. 38 and 39 N., Rs. 48 and 49 E., heretofore described. West, bet. secs. 1 and 36.

40.57 Fall 3 lks. N. of the 1/4 sec. cor. hereinafter described. The bearing of this half mile therefore is S.89°57'W., and the distance is 40.57 chs. From point 3 lks. N. of the 1/4 sec. cor., continue West, with continuous measurement.

80.58 Fall 2 lks. S. of the cor. of secs. 1, 2, 35, and 36 hereinafter described. The bearing of this half mile therefore is N.89°56'W.,