

DEPENDENT RESURVEY OF SUBDIVISION OF T.39 N., R.48 E.

Chains

- 40.65 Road, bears NE. and SW.
 70.65 Low spur, projects S.; thence over low broken mesa.
 78.00 Leave mesa, bears NE. and SW.; descend NW. slope 25 ft.
 80.20 The reconstructed original cor. of Tps. 39 and 40 N.,

Rs. 47 and 48 E. heretofore described.

Land, rolling and broken hills with general slopes to

Rock Creek which drains southwesterly.

Soil, sandy clay loam, gravelly and rocky; 2nd. to 4th.

rates.

No timber.

Undergrowth, sagebrush and native grasses.

DEPENDENT RESURVEY OF SUBDIVISION OF T.39 N., R.48 E.

REESTABLISHMENT OF SURVEYS EXECUTED
 BY HATCH, EATON, AND SMYLES, U. S.
 DEPUTY SURVEYORS IN 1873.

From the reconstructed original cor. of secs. 1, 2, 35, and
 36 on the S. bdy. of the Tp., heretofore described.

N.0°32'E., bet. secs. 35 and 36.

Gradually descend over gently rolling land sloping E.
 and draining N., through dense sagebrush undergrowth.

- 15.45 Secondary road, bears N.15°W. and S.15°E.

- 18.60 Hot Creek, 2 lks. wide, 3 ins. deep, course N.15°W.

- 25.40 Road, bears E. to Tuscarora and W. to Midas, Nevada.

- 34.96 Station No.247 of traverse of Willow Creek Reservoir,
 bears N.14°30'W., 28 lks. distant; thence across area

included in Willow Creek Reservoir.

- 38.49 The $\frac{1}{4}$ sec. cor., which is a quartzite stone, 12x8x6 ins.,
 loosely set in the ground and marked $\frac{1}{4}$ on NW. face.
 I reset cor. monument 8 ins. in the ground, marked $\frac{1}{4}$
 on W. face, and alongside same,

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground with brass cap marked

$\frac{1}{4}$

S35

S36

1930