

Dependent Resurvey of a portion of the subdivisions of
T. 35 N., R. 18 E.

Chains.
72.50 Top of same ridge, bears NW. and SE. Along broken E. slope of ridge.

74.87 Intersect the original Benson and Putnam cor. of secs. 4 and 5 on the N. Bdy. of the township, which was re-monumented with an iron post as described in the field notes of fractional T. 35 $\frac{1}{2}$ N., R. 18 E.

Land: broken and mountainous.
Soil: a heavy clay containing much rock.
Undergrowth: sage, buckbrush and deer browse.
Good growth of grass.
Timber: juniper and mahogany.

Survey of a portion of the subdivisions of
T. 35 N., R. 18 E.

From the cor. of secs. 29 and 32 on the Nevada-California State Line, hereinbefore described,
East, on a random line, bet. secs. 29 and 32.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

93.91 Intersect the cor. of secs. 29 and 32, hereinbefore described. Thence
West on a true line, bet. secs. 29 and 32.
Gradual ascent over rolling mountainous land.

29.00 Top of low spur, projects S. Desc. SW. slope 140 ft.
49.90 Dry wash, drains N. 15° W. Asc. NE. slope 40 ft.

53.91 Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\frac{1}{4} \frac{829}{1927}$$

from which a cross on ledge 10 ft. high, facing NE., bears N. 89° 59' W., 16 lks. distant.

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of the cor.

Asc. NE. slope 20 ft.