

Dependent Resurvey of a portion of the N. Bdy.

of T. 35 N., R. 18 E.

Chains. (Reestablishment of surveys executed by Deputies Benson and Putnam, under contract No. 96, in 1880.)

TRUE LINES

The original Benson and Putnam corner of Ts. 35 and 36 N., Rs. 18 and 19 E., which is a granite stone 20 x 20 x 10 ins., marked with 6 grooves on four faces, set in a mound of stone, I reconstruct by raising a mound of stone $3\frac{1}{2}$ ft. base, 2 ft. high, S. of the corner.

Thence

S. $88^{\circ} 41'$ W. on a true line, bet. secs. 1 and 36.

Desc. gradual W. slope 50 ft. over rolling and rocky mesa, through scattering juniper.

38.00 Rim of mesa bears N. 30° E. and S. 30° W. Desc. abrupt W. slope 150 ft. over volcanic outcroppings and talus to dry wash.

40.15 Intersect the original $\frac{1}{4}$ sec. cor., which is a granite stone, 18 x 16 x 8 ins., marked $\frac{1}{4}$ on N. face, set in a mound of stone. At exact corner point, over cross on exposed outcropping, with original corner alongside, set an iron post 3 ft. long, 1 in. in diam., in a mound of stone $3\frac{1}{2}$ ft. base, 36 ins. high, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S36
 $\frac{1}{4}$
S1
1928

From the $\frac{1}{4}$ sec. cor., S. $89^{\circ} 18'$ W., with continuous measurement.

44.10 Dry wash, drains N. 15° W. to main canyon.

Desc. 30 ft.

63.00 Dry wash in canyon, drains NE. Asc. abrupt E. slope 170 ft.

75.50 W. rim of canyon. Asc. 10 ft.

80.19 Intersect the cor. of secs. 1, 2, 35 and 36, which is a volcanic stone, 16 x 14 x 12 ins., marked with 5 grooves on W. face and 1 groove on E. face, set in a mound of stone. Alongside, set an iron post 3 ft. long, 2 ins. in diam., 18 ins. in the ground, to solid rock, in a