

Dependent Resurvey of the E. Bdy. of T. 33 N., R. 18 E.

Chains. N. $0^{\circ} 13'$ W. on a true line, on the E. Bdy. of sec. 1.
 Desc. gradually over rolling mesa.

5.50 A northing of 40.00 chs. from the cor. of secs. 7 and 18, hereinafter determined. Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 7 only, with brass cap mkd.

$\frac{1}{4}$
 S7
 1927

Raise a mound of stone 3 ft. base, 2 ft. high, E. of the cor.

39.93 $\frac{1}{2}$ The proportionate point. Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap mkd.

$\frac{1}{4}$
 S1
 1927

Raise a mound of stone 3 ft. base, 2 ft. high, W. of the cor.

45.50 A northing of 80.00 chs. from the cor. of secs. 7 and 18, hereinafter determined. Set an iron post 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 6 and 7 only, with brass cap mkd.

T33N
 T33N S6
 R18E S7
 S1 R19E
 1927

Raise a mound of stone 3 ft. base, 2 ft. high, E. of the cor.

Corner stands on edge of mesa, bearing E. and W.
 Desc. rocky N. slope 170 ft. into canyon.

53.20 Creek in bottom of canyon; running water 1 lk. wide, 2 ins. deep; course N. 70° E. for about 5.00 chs. thence north to main canyon. Asc. rocky S. slope 140 ft.

65.80 Top of rocky spur, projects NE. Desc. abrupt slope of canyon 240 ft.

75.00 Stream of running water in bottom of canyon; 4 lks. wide 4 ins. deep; course NE. from N. 40° W. Asc. 150 ft.