

Dependent Resurvey of the E. Bdy. of T. 33 N., R. 18 E.

Chains.
79.87

Intersect the cor. of Ts. 33 and 34 N., R. 18 E., which is a volcanic stone, 28 x 18 x 12 ins. above ground, set in a mound of stone, marked with 6 grooves on N. and S. faces. Alongside, set an iron post, 3 ft. long, 3 ins. in diam., on exposed outcropping, in a mound of stone, 6 ft. base, 36 ins. high, for the cor. of Ts. 33 and 34 N., R. 18 E., with brass cap mkd.

T34N	T33N
R18E	R19E
S36	S6
S18	S6
T33N	
1927	

Corner stands on crest of rocky spur projecting W.

Land: rolling and broken mountainous.

Soil: a heavy clay containing much rock.

Undergrowth: sage and scattering bruckbrush.

Good growth of grass.

Timber: very scattering juniper.

Dependent Resurvey of a portion of the E. Bdy. of sec. 36,

T. 34 N., R. 18 E.

(Reestablishment of surveys executed by Deputy Garside in 1880, under contract No. 93. Retracement by U.S. Surveyor H.W. Reppert in 1916, under group No. 48.)

From the cor. of Ts. 33 and 34 N.; R. 18 E., hereinbefore described,

N. 0° 16' E. on a true line, bet. secs. 6 and 36.

Desc. along rocky slope of canyon 40 ft. over mountainous land.

5.63 A northing of 40.00 chs. from the cor. of secs. 6 and 7, hereinbefore described. Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap mkd.

1
4
86
1927