

Survey of a portion of the S. Bdy. of T. 33 N., R. 19 E.

Chains. for the cor. of secs. 31 and 32, with brass cap mkd.

T33N | R19E
S31 | S32
1927

At base of post deposit a volcanic stone, 12 x 7 x 6 ins., marked with cross (x).

Land: rolling mountainous.

Soil: a heavy clay; very rocky.

Undergrowth: sage and scattering buckbrush.

Good growth of grass. No timber.

West on a true line, on the S. Bdy. of sec. 31.

Asc. SE. slope 210 ft. over rolling mountainous land.

10.10 Top of spur, projects S. Desc. 50 ft.

17.90 Dry wash, drains S. 20° W. Asc. SE. slope 240 ft. to the $\frac{1}{4}$ sec. cor.

27.70 Small spring bears S. approximately 14.00 chs.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 31 only, with brass cap mkd.

T33N | R19E
S31 | S32
1927

Raise a mound of stone 3 ft. base, 2 ft. high, N. of the cor.

Asc. SE. slope 60 ft.

54.80 Top of spur, projects S. 15° E. Desc. 65 ft.

69.70 Top of ledge 20 ft. high facing W. Desc. W. slope 170 ft.

80.04 Intersect the E. Bdy. of T. 33 N., R. 18 E., at a point, S. 0° 34' W., 33.86 chs. distant from the restored cor. of secs. 25 and 36, hereinbefore described. At the point of intersection, set an iron post 3 ft. long, 3 ins. in diam., 18 ins. in the ground, to solid rock, and 18 ins. in a mound of stone, for the closing cor. of Ts. 32 and 33 N., R. 19 E., with brass cap mkd.

T33N | R19E
R18E | S31 C
S36 | S6 C
T32N
1927