

Completion of subdivisions, T. 29 N., R. 22 E.

Chains.	Pits impracticable and no other accessories available.
	Asc. 80 ft. over rolling SE. slope.
60.00	Over nearly level land.
79.86	Intersect the N. Bdy. of the township, at a point, West, 2.42 chs. distant from the cor. of secs. 1, 2, 35, and 36, which is an iron post 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 30 N., R. 22 E. This corner now becomes a corner of two sections only, and the markings thereon, properly changed to refer to secs. 35 and 36, T. 30 N., R. 22 E.
	At the point of intersection set an iron post 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 1 and 2, with brass cap marked
	<div style="text-align: center;"> T30N R22E S35 S2 S1 T29N R22E C C 1928. </div>
	Raise a mound of stone 2 ft. base, 1½ ft. high, S. of the cor.
	Land; slightly rolling.
	Soil; medium clay loam containing some gravel and rock.
	Undergrowth; medium growth of shadscale and sage.
	Scant growth of grass.
<hr/>	
	The ¼ sec. cor. of secs. 1 and 36, on the N. Bdy. of the township, which is an iron post, 1 in. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 30 N., R. 22 E., I change to refer to sec. N36 only. Thence
	West
2.45	Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the ¼ sec. cor. of sec. 1 only, with brass cap marked
	<div style="text-align: center;"> ¼ S1 1928 </div>
	At base of post deposit a trap stone, 10 x 8 x 5 ins., marked with cross (x).

Stop