

Completion of subdivisions, T. 29 N., R. 22 E.

Chains. N. 0° 02' W.. bet. secs. 3 and 4. Asc. 5 ft. over rolling mountainous land.

3.50 Top of ridge, bears NE. and SW. Desc. 115 ft. over rolling NW. slope.

20.00 Dry wash near head, drains NW. Asc. 240 ft. over rolling SW. slope.

36.80 Top of spur, projects NW. Desc. 45 ft. over NE. slope.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked

S4 | S3
1928

Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

41.00 Top of spur, slopes NE. Desc. 325 ft. over NW. slope.

52.80 Head of dry wash, drains NW. Continue descent over broken W. slope 80 ft.

63.00 Ascend 110 ft. over SW. slope.

71.90 Saddle in crest of spur sloping NW. Desc. 125 ft. over NE. slope.

80.02 Intersect the N. Bdy. of township, at a point, West, 2.00 chs. distant, from the cor. of secs. 3, 4, 33, and 34, which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 30 N., R. 22 E. The markings on this corner changed to refer to secs. 33 and 34 only.

At the point of intersection, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 3 and 4, with brass cap marked

T30N R22E
S33
S4 | S3
T29N R22E
C C
1928

Raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the cor.