

Dependent Resurvey of a portion of the S. Bdy. of T. 33 N., R. 37 E.

Chains.

A juniper, 5 ins. in diam., bears N. $42\frac{1}{4}^{\circ}$ E., 109 lks. dist., marked T33N R37E S32 BT

A juniper, 8 ins. in diam., bears N. $38\frac{3}{4}^{\circ}$ W., 235 lks. dist., marked T33N R37E S31 BT

Land, broken and mountainous. Soil, rocky and gravelly; 3rd rate. Undergrowth, sage. Scattering juniper timber.

N. $89^{\circ} 29'$ W., on a true line, on the S. Bdy. of sec. 31.

Asc. along S. slope over broken mountainous land.

3.60 Top of spur, projects S. 30° W. Desc. SW. slope 390 ft. through juniper timber.

27.00 Dry wash, course N. 70° W. Desc. 70 ft. to $\frac{1}{4}$ sec. cor.

29.00 Old road, bears S. 70° E. and N. 70° W.

38.60 Intersect the old $\frac{1}{4}$ sec. cor., which is a juniper post, 3 ft. long, 2 ins. square, marked $\frac{1}{4}$ on N. face. Alongside, set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 31, only, with brass cap mkd.

$\frac{1}{4}$ S31

1925

from which

A juniper, 6 ins. in diam., bears N. $42\frac{1}{4}^{\circ}$ E., 280 lks. dist., marked $\frac{1}{4}$ S31 BT

A juniper, 4 ins. in diam., bears S. 69° E., 245 lks. dist., marked $\frac{1}{4}$ BT only

From the $\frac{1}{4}$ sec. cor., S. $89^{\circ} 25'$ W., with continuous measurement.

Desc. rolling west slope 300 ft. to township cor.

58.80 Leave scattering juniper timber, bears NE. and S.

78.72 Intersect the old cor. of Ts. 32 and 33 N., Rs. 36 and 37 E., which is a juniper post, 3 ft. long, 3 ins. square, marked with 3 notches on 3 faces, which were the

only legible marks, set in a mound of earth. Alongside,

set an iron post, 3 ft. long, 3 ins. in diam., 32 ins.

in the ground, for the cor. of Ts. 32 and 33 N., Rs.

36 and 37 E., with brass cap mkd.