

Dependent Resurvey of the W. Bdy. of T. 33 N., R. 37 E.

- Chains. Land, broken mountainous with numerous limestone outcroppings. Soil, rocky and gravelly clay. Undergrowth, sage and buck brush. Timber, scattering juniper.
-
- N. $0^{\circ} 43'$ W., on a true line, bet. secs. 1 and 6.
Desc. along E. slope of divide 260 ft.
- 33.30 Summit of divide, bears North and S. 10° W. Line crosses through saddle. slope 50 ft.
- 39.66 Intersect the old $\frac{1}{4}$ sec. cor. of secs. 1 and 6, which is Quartzite stone, 10 x 8 x 8 ins., marked $\frac{1}{4}$ on W. face, Alongside, set an iron post, 3 ft. long, 1 in. in diam. 24 ins. in the ground, to solid rock, and in a mound of stone, for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, with brass cap mkd.
- $$\begin{array}{c} \frac{1}{4} \\ \text{S1} \mid \text{S6} \\ 1925 \end{array}$$
- from which
- A juniper, 4 ins. in diam., bears S. $26\frac{3}{4}^{\circ}$ E., 146 lks. dist., marked $\frac{1}{4}$ S6 BT
- A juniper, 6 ins. in diam., bears S. $40\frac{1}{4}^{\circ}$ W., 30 lks. dist., marked $\frac{1}{4}$ S1 BT
- From the $\frac{1}{4}$ sec. cor., N. $0^{\circ} 02'$ E., with continuous measurement.
- Asc. S. slope 50 ft.
- 47.50 Top of divide, bears N. and S. 10° E. Spur, projects S. 70° W.
Desc. 200 ft. on top of divide, over N. slope.
- 50.50 Mine dump bears W. 50 lks. dist.
- 62.50 Road, bears NE. and SW.
- 64.00 Top of divide, bears N. 10° E. and South.
- 73.30 Top of spur, projects W. Desc. NW. slope 60 ft.
- 79.85 Intersect the old cor. of Ts. 33 and 34 N., Rs. 36 and 37 E., which is a limestone, 10 x 10 x 4 ins. above ground, firmly set in a mound of stone, marked with 6 grooves on each face. Alongside, set an iron post, 3 ft. long, 3 ins. in diam., 30 ins. in the ground, for the cor. of Ts. 33 and 34 N., Rs. 36 and 37 E., with