

Dependent Resurvey of a portion of the N. Bdy. of T. 33 N., R. 37 E.

Chains.

- 60.00 Intersect fence cor. from which fences bear N. and W.
 77.20 Old road, bears N. 10° W. and S. 10° E.
 80.42 Intersect the old cor. of secs. 4, 5, 32 and 33, which
 quartzite stone, 9 x 6 x 4 ins. above ground, marked
 with 4 grooves on E. face and 2 grooves on W. face.
 Alongside, set an iron post, 3 ft. long, 2 ins. in diam.,
 27 ins. in the ground, for the cor. of secs. 4, 5, 32
 and 33, with brass cap mkd.

T34N	R37E
S32	S33
S5	S4
T33N	
1925	

At base of post, deposit a glass memorial.

Land: E. half mile slightly rolling; W. half mile, roll-
 ing hilly. Sandy, gravelly and rocky 3rd rate soil.

Undergrowth, sage. Timber, a few scattering juniper.

 Dependent Resurvey of a portion of the subdivisions of
 T. 33 N., R. 37 E.

From the cor. of secs. 32 and 33, on the S. bdy. of the
 township, hereinbefore described,

N. 0° 31' E., on a true line, bet. secs. 32 and 33.

Asc. S. slope 130 ft. through scattering juniper and
 mahogany timber, over broken mountainous land.

- 8.50 Top of spur, projects S. 80° E. Saddle in spur about
 20.00 chs. E. of line. Desc. NE. slope 270 ft.
 22.10 Dry wash in bottom of canyon, course E. Asc. abrupt S.
 slope 380 ft. through juniper and mahogany timber.
 40.00 Top of rocky spur, projects N. 70° E. Desc. NW. slope.
 40.77 Intersect the old $\frac{1}{4}$ sec. cor., which is a limestone,
 12 x 12 x 7 ins. above ground, firmly set in a mound
 of stone, marked $\frac{1}{4}$ on E. face. Alongside, set an iron
 post, 3 ft. long, 1 in. in diam., 12 ins. in the ground,
 to solid rock, in a mound of stone, 4 ft. base, 24 ins.
 high, for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, with brass
 cap mkd.