

## Dependent Resurvey of a portion of the W. Bdy. of T. 13 N., R. 61 E.

Chains.

1 and 12, with brass cap mkd.

T13N	
S1	T13N ✓
S12	R61E
R60E	S6
	1925

from which

✓ A juniper, 3 ins. in diam., bears S. 45° W., 212 lks.  
dist., marked T13N R60E S12 BT

A juniper, 2 ins. in diam., bears N. 39½° W., 106 lks.  
dist., marked T13N R60E S1 BT

Land, slightly rolling. Soil, rocky, gravelly, clay .

Undergrowth, medium growth shadscale and sage and scant  
growth of grass. Timber, scattering juniper.

N. 0° 18' E., on a true line, on the E. Bdy. of sec. 1.

Desc. N. slope 30 ft. over rolling land.

4.60 Dry wash, course E. Asc. SE. slope 30 ft.

7.90 Top of spur, projects SE. Desc. NE. slope 50 ft.

25.00 Dry wash, course SE. Asc. S. slope 50 ft.

32.80 Top of spur, projects E. Desc. N. slope 20 ft.

✓ 35.85 A northing of 40.00 chs. from the closing cor. of secs.  
6 and 7, hereinafter determined. Set an iron post, 3 ft.  
long, 1 in. in diam., 27 ins. in the ground, for the  
¼ sec. cor. for sec. 6, with brass cap mkd.

¼	
S6	✓
	1925

from which

✓ A juniper, 3 ins. in diam., bears N. 81½° E., 179 lks.  
dist., marked ¼ S6 BT No other bearing trees available.

At base of post, deposit a sandstone, 7 x 5 x 3 ins.,  
marked with cross (x)

40.57 The proportionate point. Set an iron post, 3 ft. long, 1  
in. in diam., 24 ins. in the ground, to solid rock, and  
10 ins. in a mound of stone, for the ¼ sec. cor. for  
sec. 1, with brass cap mkd.

¼	
S1	✓
	1925