

DEPENDENT RESURVEY OF EAST BOUNDARY, T. 41 N., R. 22 E.

Chains

Alongside the original cor. ...
Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for the reconstructed cor. secs. 13, 18, 19
and 24, with brass cap marked.

T41N	R22E	R23E
S13	S18	S19
S24	S19	

1925

Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.
Land, rolling and broken, with a general easterly
exposure and drainage.

Soil, shallow, sandy loam mixed with decomposed lava
and lava rock; 3rd rate.

Undergrowth, dense short sagebrush.

No timber.

Fair grazing.

DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 41 N., R. 22 E.

REESTABLISHMENT OF SURVEY EXECUTED BY G. W. GARSIDE AND
C. S. PREBLE UNDER CONTRACT NO. 61, IN YEAR 1874.

From the cor. secs. 5, 6, 31 and 32, on the N. bdy. of
the township, which is hereinafter described.

West, on retracement line bet. secs. 6 and 31.

41.63

Fall 33 lks. S. of the original 1/4 sec. cor. secs. 6 and
31, hereinafter described.

The course of this half mile therefore is, N. 89°33' W.,
and the distance is 41.63 chs.

Offset to the 1/4 sec. cor. and continue W., with continuous
measurement.

82.84

Fall 79 lks. S. of the original cor. Ts. 41 and 42 N.,
Rs. 21 and 22 E., hereinafter described.

The course of this half mile therefore is, N. 88°54' W.,
and the distance is 41.22 chs.

Thence, from the cor. secs. 5, 6, 31 and 32, which is a