


DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 41 N., R. 22 E.

Chains

lava, 20 x 16 x 8 ins., loosely set in a mound of stone, marked 5 grooves on E. face, 6 grooves on N. face, and 1 groove on W. face, and unwitnessed.

Alongside the original cor. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the reconstructed cor. secs. 5, 6, 31 and 32, with brass cap marked.



1925

Raise a mound of stone, 3 ft. base, 2 ft. high W. of cor.

Thence, N. 89°33' W., on resurvey line along the N. bdy. of the township, bet. secs. 6 and 31.

Over rolling and broken land through dense short undergrowth. Ascend gradual SE. slope.

6.50 Top of descent over gradual SW. slope.

11.30 Small wash, drains SE.; ascend gradual E. slope.

41.63 The original 1/4 sec. cor. secs. 6 and 31, which is a lava, 16 x 12 x 4 ins., loosely set in a mound of stone, marked 1/4 on N. face and unwitnessed.

Alongside the original cor.

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock and 18 ins. in a mound of stone, for the reconstructed 1/4 sec. cor. secs. 6 and 31, with

brass cap marked.



1925

No other suitable accessories available.

Thence, N. 88°54' W., with continuous measurement.

43.60 Low spur, projects N. 70° E.

51.60 Small ravine, drains N. 60° E.

55.50 Rocky point, projects S., 60 ft. above ravine; continue ascent.