

Dependent resurvey of subdivision, T. 41 N., R. 22 E.

- Chains. S61S5
1925
- Raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.
From this cor., spring at head of Little Highrock Creek,
N. $56^{\circ} 30'$ W., Thence N. $0^{\circ} 54'$ E. with continuous measurement.
- 50.20 Little Highrock Creek; stream of good water, 4 lks. wide,
3 ins. deep, course E. 10.00 chs. thence N. 15° E.
- 68.00 Small ravine, drains SE.
- 81.08 The cor. of secs. 5, 6, 31 and 32.
Land, rolling. Soil, shallow, loose sand and clay loam,
mixed with decomposed lava and limestone. Undergrowth,
sage and shadscale. Fair growth of grass.
- Subdivision, T. 41 N., R. 22 E.

- From the standard cor. of secs. 35 and 36, on the S. Bdy.
of the township, hereinbefore described,
North, on sectional guide meridian, bet. secs. 35 and 36.
Over rolling land, through dense undergrowth.
- 18.30 Small ravine; drains NE.
- 35.00 Point of spur, projects N. 25° E.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 22 ins. in
the ground to bed rock and 8 ins. in a mound of stone,
for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
- S351S36
1925
- At base of post deposit a limestone, 4 x 3 x 1 ins., with
cross marked (x).
- 49.40 Top of rimrock bears SE. and N. 30° W.
- 49.70 Base of rimrock, bears SE. and N. 30° W.
- 51.20 Top of rimrock, bears NW. and SE.
- 52.80 Base of rimrock, bears NW. and SE.
- 54.20 Wash, 30 lks. wide, 2 ft. deep in canyon, 360 ft. below
the $\frac{1}{4}$ sec. cor., drains S. 80° E.; asc. gradual S. slope.
- 55.10 Base of rimrock, bears N. 80° W. and S. 60° E. Break in
the rim rock bears East, 75 lks. dist.
- 55.60 Top of rimrock, bears N. 80° W. and S. 60° E.