

Measurements

slope measurements properly reduced to true horizontal distances.

PROCEDURE

Prior to the reestablishment of the west boundary of fractional T. 44 N., R. 24 $\frac{1}{2}$ E. retracements were made along the north boundary of T. 44 N., R. 25 E., the S. Bdy. of T. 45 N., R. 24 E. and the E. Bdy. of T. 44 N., R. 24 E. and the reestablished point for the original corner of Ts. 44 and 45 N., Rs. 24 and 25 E. was determined by proportionate measurement under control of the original corner of Ts. 44 and 45 N., Rs. 23 and 24 E. and the corner of Ts. 43 and 44 N., Rs. 24 and 25 E. and the cor. of Tps. 44 and 45 N., Rs. 25 and 26 E. The record of the retracements necessary in connection with this reestablishment appears in book "A" of the field notes of the survey of T. 45 N., R. 24 E., Group 134, Nevada.

The bearing of the line bet. the cor. of Ts. 43 and 44 N., Rs. 24 and 24 $\frac{1}{2}$ E. and the reestablished point for the cor. of Ts. 44 and 45 N., R. 24 E. is N.0° 14' W. and the proportionate length of each one-half mile is 40.00 chs.

DEPENDENT RESURVEY OF THE E. BDY. OF T. 44 N., R. 24 E.
REESTABLISHMENT OF SURVEYS EXECUTED BY G.W.GARSDIE, U.S.
DEPUTY SURVEYOR IN 1877

Chains

From the cor. of Ts. 43 and 44 N., Rs. 24 and 24 $\frac{1}{2}$ E.; which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 43 N., R. 24 $\frac{1}{2}$ E., set alongside the original corner of Ts. 43 and 44 N., Rs. 24 and 25 E. N. 0° 14' W., on a true line, bet. secs. 35 and 36.

Asc. S. slope over rolling mountainous land.

30.00

Top of ridge, bears E. and W. Desc. gradual N. slope
20 ft.