

Independent Resurvey of Second Standard Parallel North  
Through Range 28 East

Independent Resurvey of Second Standard Parallel North  
Through Range 28 East

Chains	REESTABLISHMENT OF SURVEYS EXECUTED BY CHASE AND LASH, U. S. DEPUTY SURVEYORS UNDER CONTRACT No. 4, IN 1867.
	From the Standard Cor. of T. 11 N., Rs. 27 and 28 E., which is a 3 in. iron post, firmly set in the ground, and marked and witnessed as described in the official records of the survey of T. 11 N., R. 27 E. East, on independent resurvey along S. boundary of sec. 31 Over rolling land
2.30	Wash, 50 lks. wide, 3 ft. deep, drains S. 65° W. Asc. gentle NW. slope 70 ft. to
17.20	Low flat spur, projects S. 45° W. Desc. along gentle SE. slope
22.30	Shallow draw, drains S. 45° W. Asc. gentle NW. slope 80 ft. to 43.20
32.35	Wash, 55 lks. wide, 3 ft. deep, drains S. 50° W.
40.00	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd $\frac{1}{4}$ S 31 1929
40.50	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Fall 3 lks. S. of the old standard $\frac{1}{4}$ sec. cor., which is a trap stone, firmly set in mound of earth and stone, and marked and witnessed as described in original field notes, I destroy all trace of same
43.20	Low spur, projects S. 50° W. Asc. along S. slope
52.80	Wash, 20 lks. wide, 2 ft. deep, drains S. 55° W. Asc. NW. slope 40 ft. to
59.70	Low spur, projects S. 60° W. Asc. along S. slope 65 ft. to 79.40
72.80	Unused road, bears S. 75° W. and NE. I destroy