

T. 11 N., R. 29 E.

I examine the adjustments of the transit and correct all errors.

The instrument is tested at frequent intervals on true meridians and is personally kept in adjustment throughout the progress of the survey.

INDEPENDENT RESURVEY OF SECOND STANDARD PARALLEL NORTH
THROUGH RANGE 29 EAST

REESTABLISHMENT OF SURVEYS EXECUTED BY
CHASE AND LASH, U. S. DEPUTY SURVEYORS
UNDER CONTRACT No. 4, IN 1867.

Chains From the Standard Cor. of T. 11 N., Rs. 28 and 29 E.,
as described in official records of Independent
Resurvey of Second Standard Parallel North in "Book
A", under Group No. 124, made in conjunction with the
survey of this township Whence
Mt. Grant U.S.G.S. Station bears S. 0° 11' W.
East, on independent resurvey on S. boundary of sec. 31

Over rough mountainous land

Desc. steep rocky NE. slope 160 ft. to

11.00 Ravine, drains S. 20° E.

Asc. steep rocky SW. slope 565 ft. to spur

17.75 Wash, 40 lks. wide, 5 ft. deep, drains S., heads about
15 chs. N.

29.65 Spur, projects S. 30° E.

Desc. SE. slope 355 ft. to 52.70

38.60 Spur, projects S. 20° E.

40.00 Find no trace of old standard $\frac{1}{4}$ sec. cor.

Set an iron post, 3 ft. long, 1 in. dia., 6 ins. in the
ground to solid rock, in a mound of stone, for the
standard $\frac{1}{4}$ sec. cor., with brass cap mkd

SC

$\frac{1}{4}$ S 31

At base of post deposit a mkd (X) granite stone, 8x8x12 ins.

52.70 Head of draw, drains S. 20° E.

Asc. SW. slope 85 ft. to