

Dependent Resurvey of Portion of North Boundary

T. 11 N., R. 29 E.

Chains	Thence
	On same line with continuous measurement along S. boundary of sec. 31
120.69	Fall 3 lks. S. of the old $\frac{1}{4}$ sec. cor., hereinafter described
	True Lines.
	I reestablish the cor. of T. 12 N., Rs. 28 and 29 E., by proportionate three point control, with an iron post, 3 ft. long, 3 ins. dia., set 18 ins. in the ground to solid rock, in a large mound of stone, with brass cap mkd
	T12N R28E R29E S36 S31 S1 T11NR28E 1929
	At base of post deposit a mkd (X) granite stone, 6x6x6 ins. Cor. sets in gravelly bottom of wash, draining NE.
	From the above cor. the $\frac{1}{4}$ sec. cor., between Secs. 31 and 36 bears N. 0° 13' E., 40.00 chs., and the cor. of Secs. 1, 2, 35 and 36, bears N. 89° 59' W. 80.46 chs.
	Thence
	N. 89° 55' E., along S. boundary of sec. 31
	Over rolling land
	Gentle ascent from wash
1.35	Point of spur, projects NE.
	General descent
4.96	Point for closing cor. of Ts. 11 N., Rs. 28 and 29 E., hereinafter described
10.15	Wash in bend, drains NE. from NW.
23.65	Broad surface wash, drains S. 45° E.
26.40	Main Walker Highway, N. to Yerington and S. to