

Survey of Second Standard Parallel North  
Through Range 29 East.

Chains	From the standard cor. of secs. 31 and 32 East, on S. boundary of sec. 32
	Over rough mountainous land
	Precipitous descent of NE. slope over rock slides and ledges 460 ft. to
10.30	Base of ledges
	Desc. steep rocky broken NE. slope 225 ft. to
18.60	Canyon, drains S. 45° E.
	Asc. broken SW. slope 165 ft. to
21.75	Desc. short SE. slope 15 ft. to
23.50	Short side hill draw, drains SE.
	Asc. SW. slope 20 ft. to
28.75	Desc. SE. slope 475 ft. meander cor.
40.00	Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd
	<div style="text-align: center;">           SC  <math>\frac{1}{4}</math> S 32  <hr/>           1929         </div>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
	Station Mt. Grant U. S. G. S., bears S. 6° 37' W.
46.05	Wash, 40 lks. wide, 4 ft. deep, drains S. 45° E.
	Thence over rolling land
66.00	Main Walker Lake Highway, bears NE. to Yerington and SW. to Hawthorne
66.60	East end of concrete culvert, bears 35 lks. N. of line
77.52	Mean high water mark of Walker Lake
	Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the standard meander cor. of sec. 32, with brass cap mkd
	<div style="text-align: center;">           SC            T11NR29E            S 32  <hr/>           1929 / MC         </div>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Land, rough mountainous to rolling. Soil, rocky.
	Timber, none. Undergrowth, sage.
	General drainage, SE. Grazing, poor.