

Subdivisions T. 11 N., R. 29 E.

Chains Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the meander cor. of secs. 28 and 33, with brass cap mkd

T11N
S28

S33
R29E
1929
MC

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, mountainous and rolling. Soil, sandy gravel.

Timber, none. Undergrowth, none.

General drainage, E. Grazing, none.

From the cor. of secs. 20, 21, 28 and 29

East, between secs. 21 and 28

Over rolling land

25.00 Desc. gentle E. slope

36.00 Mean High Water Mark of Walker Lake

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the meander cor. of secs. 21 and 28, with

brass cap, mkd
T11N
S21

S28
R29E
1929
MC

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling. Soil, sandy.

Timber, none. Undergrowth, none.

General drainage, E. Grazing, none.

MEANDERS, T. 11 N., R. 29 E.

From the standard meander cor. of frac. sec. 32, on

S. boundary of township

With meanders in sec. 32

Along level beach

N. $24^{\circ} 19'$ E., 6.15 chs. To meander cor. of frac. secs.

32 and 33

Land, level. Soil, sand.

Timber, none. Undergrowth, none.