

## Mineral Segregation Survey in T. 32 N., R. 31 E.

## General Method of Procedure

## Chains

Cor. No. 1 of the claim was established by running along the lode line from the location monument, S. 39° 43' W., 750-ft. to center of end line, thence along said line N. 50° 17' W., 300 ft., at which point

Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the ground to solid rock, in a mound of stone, with brass cap mkd

1  
MV

1929

At base of post deposit a mkd(X) basalt stone, 3x4x4 ins.

The cor. of secs. 10, 11, 14 and 15, bears S. 61° 30' W.

9.663 chs.

Thence

N. 39° 43' E., on line 1-2

Over mountainous land

Asc. rocky NW. slope

1.650 Desc. steep rocky NE. slope

22.727 Cor. No. 2

Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the ground to solid rock, in a mound of stone, with brass cap mkd

2  
MV

1929

At base of post deposit a mkd(X) basalt stone, 3x6x8 ins.

Thence

S. 50° 17' E., on line 2-3

Over mountainous land

Asc. steep rocky NE. slope

9.090 Cor. No. 3

Set an iron post, 3 ft. long, 1 in. dia., 16 ins. in the ground to solid rock, in a mound of stone, with brass cap mkd

MV  
3

1929

At base of post deposit a mkd(X) slate stone, 3x6x8 ins.

Thence