

## Retracement of Outboundaries, Sec. 12, T. 34 N., R. 34 E.

3

## Chains.

1 in. in diam., 18 ins. in the ground, to solid rock, and 18 ins. in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S1
$\frac{1}{4}$ ———
S12
1925

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of the cor.

The course of this  $\frac{1}{2}$  mile is N.  $89^{\circ} 56'$  E. and the dist. is 40.37 chs.

80.48 Fall 80 lks. N. of the cor. of secs. 1, 6, 7 and 12, which is a basalt stone, firmly set in a mound of stone, 14 x 10 x 8 ins. above ground, marked with 5 notches on S. face and 1 notch on N. face. Alongside, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

T34N
R34E   R35E
S1   S6
S12   S7
1925

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of the cor.

From this point, a redwood post, 20 ins. long,  $2\frac{1}{2}$  ins. square, marked with 5 notches on one face, 1 notch on one face, and T34N S6 S12, set in a mound of stone, bears N.  $5^{\circ} 30'$  E., 89 lks. dist.

The course of the E.  $\frac{1}{2}$  mile is S.  $88^{\circ} 47'$  E., and the dist. is 40.12 chs.

-----

From the cor. of secs. 1, 6, 7 and 12, South, on retracement, bet. secs. 7 and 12.

39.27 Fall 15 lks. W. of the  $\frac{1}{4}$  sec. cor., which is a limestone, firmly set, 12 x 8 x 6 ins. above ground, marked  $\frac{1}{4}$  on W. face. Alongside is a willow post, 2 ins. in diam., 3 ft. long. Pits N. and S. of cor.

The course of this  $\frac{1}{2}$  mile is S.  $0^{\circ} 13'$  E., and the dist. is 39.27 chs.