

Survey of the Keystone Lode.

Chains.

Identical with the NW. location cor., set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, for cor. No. 3 of the Keystone lode, with brass cap mkd.



1925

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, within the claim, bisecting line formed by the side and end.

Thence S. $55^{\circ} 55'$ E.

4.015 Intersect lode line, at a point, N. $29^{\circ} 13'$ E., 13.568 chs. dist. from the location monument on the lode line, which is a post, 4 ins. square, 4 ft. above ground, set in a mound of stone, with location notice attached.

8.21 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins. in the ground, to solid rock, and 12 ins. in a mound of stone, for cor. No. 4 of the Keystone lode, with brass cap mkd.



1925

from which the NE. location cor. bears N. $22^{\circ} 31'$ E.,

1.38 chs. dist. From cor. point, the $\frac{1}{4}$ sec. cor. of secs. 1 and 12 bears S. $53^{\circ} 21'$ E., 13.96 chs.

Thence S. $27^{\circ} 35'$ W.

9.42 Intersect sec. line bet. secs. 1 and 12, at a point, S. $89^{\circ} 56'$ W., 15.59 chs. dist. from the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.


12.79 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for cor. No. 5, of the Keystone lode, with brass cap mkd.



1925

Thence S. $18^{\circ} 47'$ W.

7.63 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, for cor. No. 6, of the Keystone lode, with brass cap mkd.



1925