

SUBDIVISION OF T. 24 N., R. 67 E.

Chains

- N. 89° 56' W., on a true line, bet. secs. 3 and 10.
Over rough and broken mountain land, thru medium dense timber and undergrowth. Desc. 90 ft. over precipitous SE. slope.
- 4.00 Wash, in bottom of draw, 10 lks. wide, 1 ft. deep, course SE.; asc. 285 ft. over NE. slope.
- 13.50 Spur, projects NE.; desc. 70 ft. over NW. slope.
- 27.75 Wash, in bottom of draw, 10 lks. wide, 3 ft. deep, course NE. This is the same draw heretofore described at 4 chs. on this line. Asc. 105 ft. over broken S. slope.
- 40.07 On broken S. slope
Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked
- | | |
|---------------|-------|
| | S 3 |
| $\frac{1}{4}$ | ----- |
| | S 10 |
| | 1926 |
- and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of the post.
- No other suitable accessories available.
Continue asc. 535 ft. over broken S. slope.
- 80.14 The cor. of secs. 3, 4, 9 and 10.
Land, broken mountain land; general drainage E.
Soil, rocky, gravelly clay loam; 3rd rate.
Timber, mahogany, pinon pine and juniper.
Undergrowth, sagebrush and native grasses.
Good grazing.
-
- N. 0° 20' E., on a random line, bet. secs. 3 and 4.
- 40.00 Set temp $\frac{1}{4}$ sec. cor.,
- 79.37 Intersect N. bdy. of the township, 92 lks. W. of the cor. of secs. 3, 4, 33 and 34, which is an iron post, 2 in. in diam., heretofore described. Falling shows the cor.